

## PERMAPRESS BOILING KETTLES

## CombiLine 750

**• Patented, low-maintenance, closed PERMAPRESS system**

- Double-walled lid
- Inner pan made of CrNiMoTi steel 1.4571
- Inner pan emptied via safety discharge valve DN 40 (1 ½")
- Cover plate drained via overflow pipe
- Water inlet via a lid-operated swivel tap, mixing tap with cold and hot water valve DN 20 (¾")
- Filling level markings with 10-litre graduations in the pan wall
- Manual control of the food temperature
- Knob to switch from initial cooking level to simmering level



	OES 060	OES 080	OES 100
Overall dimensions, W x D x H in mm	700 x 750 x 900	800 x 750 x 900	900 x 750 x 900
Weight in kg	95	110	115
Electrical connection in kW 400 V 3 N AC 50 Hz	12.6	15.6	18.6
Usable capacity in litres	63.5	81	109
Inner pan diameter in mm	484	484	584
Inner pan height in mm	410	503	470
Boiling time, determined to DIN 18855, in minutes	25	32.5	31.5
Fast boiling pan to DIN 18855	●	●	●

**STANDARD ACCESSORIES**

1 strainer	●	●	●
------------	---	---	---

**ACCESSORIES**
**Standard fittings for inserts**

ZUB 320 1 pair of lifting hooks	○	○	○
ZUB 322 Support ring for inserts	○	○	
ZUB 323 Support ring for inserts			○

**Inserts, 8 mm perforation (up to 2 inserts per appliance)**

ZUB 382 1 insert Ø 465 mm, height 150 mm	○	○	
ZUB 384 1 insert Ø 565 mm, height 180 mm			○

**Inserts, 2.5 mm perforation (up to 2 inserts per appliance)**

ZUB 392 1 insert Ø 465 mm, height 150 mm	○	○	
ZUB 394 1 insert Ø 565 mm, height 180 mm			○

○ = Optional