

PERMAPRESS BOILING KETTLES - RECTANGULAR

Innovative KCI touch panel control

· Low-maintenance, closed PERMAPRESS system

- KCI touch panel behind 4 mm thick safety glass, flush-mounted
- Electronic temperature controls with target and actual temperature display and 4 fast activation settings each for the cooking time and temperature
- Double-walled lid, spring-released and balanced with all-round seal made of temperature-resistant elastomer
- Inner pan made of CrNiMoTi steel 1.4571
- Inner pan emptied via safety discharge valve DN 50 (2")

• Use of VAR 040 extends length of appliance by 100 mm

- Cover plate drained via overflow pipe
- Water inlet via a lid-operated swivel tap, mixing tap with cold and hot water valve
- Filling level marking with 10-litre graduations
- Continuous cooking mode
- RS 485 interface
- Built-in contactors



FER 300



FER 400



FER 500

0

Overall dimensions, W x D x H in mm	1600 x 850 x 900	2100 x 850 x 900	2400 x 850 x 900
Weight in kg	256	322	425
Electrical connection in kW 400 V 3 N AC 50 Hz	36.6	42.6	54.5
Usable capacity in litres	294	422	500
Dimensions of inner pan W x D x H in mm	1150 x 660 x 435	1650 x 660 x 435	1955 x 660 x 435
Capacity of inserts GN 1/1, 200 mm	8 units	12 units	14 units
Boiling time, determined to DIN 18855, in minutes	43	48	55
STANDARD ACCESSORIES			
1 strainer	•	•	•
2 stainless-steel-clad pressure hoses for drinking water TOP OPTIONS	•	•	•
	•	•	•
TOP OPTIONS VAR 020 Volume-regulated water intake device • Water automatically filled to the exact litre • Rapid selection of various filling quantities with a KCI touch panel	• •	• • •	• • •

O = Optional

ACCESSORIES

ZUB 679 Container support
ZUB 680 Container support
ZUB 681 Container support