

## GAS RECTANGULAR BOILING KETTLES – ADVANCED GAS TECHNOLOGY

## PremiumLine 850

- **Innovative KCI touch panel control**
- **Gas blower technology for maximum effect and economy**
- **KCI** touch panel behind 4 mm thick safety glass, flush-mounted
- Electronic temperature controls with target and actual temperature display and 4 fast activation settings each for the cooking time and temperature
- Double-walled lid, spring-released and balanced with all-round seal made of temperature-resistant elastomer
- Inner pan made of CrNiMoTi steel 1.4571
- Inner pan emptied via safety discharge valve DN 50 (2")
- Cover plate drained via overflow pipe
- Water inlet via a lid-operated swivel tap, mixing tap with cold and hot water valve
- Filling level marking with 10-litre graduations
- Continuous cooking mode
- RS 485 interface



	<b>FLR 300</b>	<b>FLR 400</b>
Overall dimensions, W x D x H in mm	1700 x 850 x 900	2200 x 850 x 900
Weight in kg	340	376
Nominal heat load in kW natural gas E, 20 mbar	43	54
Electrical connection in kW 230 V 1 N AC 50 Hz	0.15	0.15
Usable capacity in litres	294	422
Dimensions of inner pan W x D x H in mm	1150 x 660 x 435	1650 x 660 x 435
Capacity of inserts GN 1/1, 200 mm	8 units	12 units
<b>Heating-up time in minutes according to DIN 18855</b>	<b>36</b>	<b>42</b>

### STANDARD ACCESSORIES

1 strainer	●	●
2 stainless-steel-clad pressure hoses for drinking water	●	●
1 stainless-steel-clad safety gas tube	●	●



### TOP OPTIONS

#### VAR 020 Volume-regulated water intake device

- Water automatically filled to the exact litre
- Rapid selection of various filling quantities with a **KCI** touch panel
- Automatic filling process stop

○

○

#### VAR 808 Core temperature probe

- Cooking to perfection
- Rapid selection of various temperatures with a **KCI** touch panel
- Save on energy through optimal cooking time

○

○

### ACCESSORIES

ZUB 791 Double jacket for fume vent, for upgrading appliance	○	○
ZUB 679 Container support	○	
ZUB 680 Container support		○
Injector sets for different gas types	see page 67	see page 67

○ = Optional